

**WIRELESS MICROPHONE SYSTEM****MSUF SC 9120**

D03-51-MSUF SC- V310308

Page 1/1

**DESCRIPTION****UHF PLL-Synthesized Diversity Wireless Microphone System including :****Receiver features**

- 1/2 19" Receiver with 16 factory preset user-selectable UHF frequencies from 600 - 900MHz per 20 MHz bandwidth.
- High sensitivity and excellent image rejection.
- $\pm 40$  KHz peak deviation
- Pilotone Control
- XLR (balanced) and line (unbalanced) outputs for each receiver.
- RF test fonction.

**Transmitter features**

- 16 factory preset user-selectable UHF frequencies from 600-900MHz per 20MHz bandwidth
- $\pm 40$  KHz peak deviation
- Pilotone Control
- Very low spurious emission passed the stringent CE & FCC regulations.
- Changeable Dynamic or Condenser microphone capsule.
- No handling noise in handheld with condenser capsule.
- Handheld housing coated with rubberized paint for smooth holding.
- Two-stage Sensitivity switch.
- Rotary swich channel selector.
- Low current consumption.
- Color ring on handheld microphone identifies channel.
- 4-pin Min - XLR connector.

The kit **MSUF SC** (Code : 9120) included :One wireless receiver **RSF1816 SC** and a Hand-held Wireless Microphone **MSF5016**.**RSF 1816 SC  
Code : 9117**

<b>RSF1816 SC</b>	<b>9117</b>
<b>Band of frequency</b>	<b>UHF</b>
<b>Number of channel</b>	<b>16</b>
<b>Type of reception</b>	<b>Diversity</b>
<b>Power supply</b>	<b>10 - 15V / 800mA</b>
<b>Dimension</b>	<b>1/2 19" Casing</b>

**ACCESORIES****HEADPHONE****MCY 72  
Code : 9114****MICROPHONE LAVALIER****MCY 16 SC  
Code : 9124****BODY TRANSMITTER****LSF5016  
Code : 9119****ANTENNA****UA-800  
Code : 9121****BATTERY MICROPHONE ADAPTATOR 9VDC / 700mA****HCY 30  
Code : 9122****Rack mounting 19" : KHF01 (Code : 8760)****BATTERIES****3 Batteries****BATTERY MICROPHONE****TYPE AA (RL06)****2 Batteries****LSF 5016  
Code : 9119**